





CLASSIFICATION		POWER RELAY	
MODEL		MK2P	MK3P
APPEARANCE			
MOUNTING & SOCKET		PF083A PF083A-E	PTF113A PTF113A-E
DESCRIPTION	PLUG-IN TERMINAL		
	PC-BOARD TERMINAL		
	WITH LED PLUG-IN		
	WITH LED PC-BOARD		
CONTACT	CONTACT FORM	DPDT(2C)	3PDT(3C)
	CONTACT MATERIAL	Ag Alloy	
	RATED LOAD(RESISTIVE)	10A/ 250VAC 10A/ 30VDC	
	ELECTRICAL LIFE	10 ⁵ times	
	MECHANICAL LIFE	10 ⁷ times	
COIL	RATE VOLTAGE	DC(V): 6, 12, 24, 48, 110, 120V AC(V): 6, 12, 24, 48, 110/120, 220/240V	
	POWER CONSUMPTION	DC Coil: 1.5W AC Coil: 1.9~2.8VA	
	PICKUP VOLTAGE	AC 80% Max. DC 80% Max.	
	DROPOUT VOLTAGE	AC 30% Max. DC 10% Max.	
DIELECTRIC STRENGTH	BETWEEN CONTACT & COIL	2500VAC / 1Min	
	BETWEEN CONTACT	1200VAC / 1Min	
INSULATION RESISTANCE		≥100MΩ (500VDC)	
AMBIENT TEMPERATURE		-10℃~ +55℃	
AMBIENT HUMIDITY		45~85%RH	
WEIGHT		73g	81g
DIMENSIONS(mm)			
CONNECTION DIAGRAMS		